



Techmo Imper 500

Poliuretano

Based waterproofing component polyurethane, weatherproof and high elasticity. When polymerized elastomeric membrane forms a continuous

Applications:

Techmo Imper 500 is specially developed for waterproofing treatment horizontal surfaces.

It can be applied on different types of media: concrete, mortar, brick, bitumen, cement, steel, aluminum, terraces, balconies, gutters, tanks water, bathrooms, stairs, etc., including pavements pedestrian traffic.

Physical and chemical properties:

- High elasticity.
- Weatherproof and UV rays.
- Good adhesion to many surfaces.
- Resistant to cracking of the support.
- Impact resistant.
- Quick drying and rapid installation

Technical data:

Test	Units	Specification
dry matter	%	87
Viscosity at 20 ° C	MPa.s	500
Flash point (closed cup)	° C	> 47
Recoat time	Hours	4
Temperature Stability	° C	-50 To +90
Shore hardness A		70
Tensile	kp/cm2	105
elongation	%	450

Performance:

The approximate consumption is 2 kg/m², to a thickness of 1.6 mm. It should be applied in two coats. is advisable apply two different colors to distinguish the first second hand.

Method of application and cleaning:

It can be applied by brush, roller or airless spray bruza. The cleaning of the machinery and tools of application should made upon completion of product application using Solvent Techmo SA 100, in no case use disolventa other, since the product will not catalyze.

Drying:

- Four hours for recoating.
- Eight hours walkable.
- A day to get all the properties of the membrane.

Instructions for use:

Mix the product by gentle mixing.

Let stand a few minutes to avoid air bubbles.

Application of two coats of Techmo Imper 500 with a total yield of 2 kg/m². If deemed necessary the dilution of the product, in order to adjust the viscosity, TECHMOPOL DISOLVENTE SA 100.

We recommend using the product in its entirety after opening.

Presentation:

Available in packs of 25 kg, the colors available are gray, and red tile, for other colors (white, green, black and snuff), consult our Commercial

NOTE:

The information and technical data given here are intended for guidance only and are subject to change without notice. They are based on data and knowledge considered to be true and accurate. However, we have control over the conditions under which our products are transported, stored, handled or used by our customers. by Therefore, our guarantee is limited exclusively to product quality. none information or recommendation construed to violate any applicable rule or statute.



Techmo Imper 500 Poliuretano

Based waterproofing component polyurethane, weatherproof and high elasticity. When polymerized elastomeric membrane forms a continuous

NOTA:

La información y datos técnicos aquí reflejados son de carácter orientativo y están sujetos a posibles modificaciones sin previo aviso. Están basados en datos y conocimientos que se consideran ciertos y precisos. Sin embargo no tenemos control alguno sobre las condiciones bajo las cuales nuestros productos son transportados, almacenados, manipulados o utilizados por nuestros clientes. Por ello nuestra garantía se limita exclusivamente a la calidad del producto. Ninguna información o recomendación de interpretarse de forma que vulnere cualquier norma o disposición legal vigente.